

# Reliable Operation of Heterogeneous Wireless Networks with SON (Self-Organizing Networks) - Self-Configuration

Henning Sanneck, Szabolcs Nováczki

**Nokia Siemens Networks**  
- Research

**Tutorial DRCN** 9<sup>th</sup> International Conference on  
Design of Reliable Communication Networks




# Self-Configuration

## High-level process


- Physical Cell ID (PCI) allocation
- Neighbour Relationship (NR) planning
- Initial TXP/Tilt setting

*\*AGP: Automatic Generation of initial power/tilt Parameters*





# Auto-connectivity and -commissioning

## Motivation




**Self-configuration**




# Auto-connectivity and security setup

## Message flow




# Multi-vendor auto-connectivity

## 3GPP SA5 work item – in progress




# Multi-vendor auto-connectivity



- Generic **<server>.mediator.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org** name is resolved via DNS to actual server IP address (for CA server, vendor-specific DM „mediator“)
- **no pre-configuration, only basic DHCP operation required**
- **instead of NM-level ACS, redirection to vendor-specific DM**
- **Low overhead, multi-vendor solution; Work item recently accepted in 3GPP SA5**

# Multi-vendor Self-Configuration process control


## 3GPP SA5 Self-configuration Management (ScM) IRP



# Dynamic Radio Configuration

## Motivation

SON functions shall minimize the radio planning (but not replace it completely)





# Dynamic Radio Configuration

## Incremental Radio Network Build & Growth


SON functions enable an incremental radio network build and growth scenario, in which eNodeB/cells are inserted in an operational E-UTRAN one-by-one

- Without SON functions
  - Multiple network plans needed corresponding to each intermediate insertion step, in order to optimal configure the new eNodeB/cell and its neighbors
  - eNodeB/cell insertion needs to be coordinated; which eNodeB/cell is inserted first, which second, etc.
  - Drive tests needed after every insertion step
- With SON functions
  - Self-configuration → No intermediate planning needed
    - Optimal configuration for the current network topology
  - MDT / Self-optimization → Fewer drive testing needed
  - eNodeB/cells can be inserted in a (more or less) uncoordinated way

# Dynamic Radio Configuration

## High-level process

Computation of (continuous value) default cell parameters as baseline for self-optimization  
(cf. EU FP7 SOCRATES „Automatic Generation of Default Parameters“ (AGP) use case)



Computation of (discrete value) cell configuration parameters

Algorithm

Intermediate result


# Dynamic Radio Configuration

## Configuration Parameter Classification

„Class A“: parameters with single cell scope, >80% of all parameters, out of DRC scope

„Class B“:

B1	Uniform value <ul style="list-style-type: none"> <li>• <u>Out of scope of DRC</u>, set by the operator</li> <li>• <i>PLMN ID, Frequency band, EARFCN, #PRB</i></li> </ul>
B2	Unique value <ul style="list-style-type: none"> <li>• Straight-forward algorithms</li> <li>• Network wide inputs needed</li> <li>• <i>EGCI, eNodeB name</i></li> </ul>
B3	Collision free value with neighboring cell <ul style="list-style-type: none"> <li>• Often additional constraints apply</li> <li>• <i>PCI, PRACH root-sequence index, RS CS</i></li> </ul>
B4	Value aligned with neighboring cell(s)
B4.1	<ul style="list-style-type: none"> <li>• one-to-many relationship</li> <li>• <i>Tx Power, antenna parameters, Tracking Area</i></li> </ul>
B4.2	<ul style="list-style-type: none"> <li>• one-to-one relationship</li> <li>• <i>cell specific mobility offsets</i></li> </ul>



# Physical Cell ID (PCI) allocation

## Overview

- PCI allows fast cell identification on layer 1; Configuration constraint: only 504 PCI available
- Avoid reconfiguration overhead in operational cells as much as possible, because this leads to a service interruption
  - Reconfiguration of an PHY-CID cannot be totally avoided in an incremental network growth scenario (cf. “gets confused case”) → algorithm should consider this pro-actively in the allocation strategy
  - If a PHY-CID reconfiguration is needed, the number of cells to be reconfigured should be kept to a minimum

- Safety margin (SM)

- the **adjacency graph** is composed of cells as nodes and edges between neighbor cells
- the SM specifies a range around each cell (number of hops) in the adjacency graph in which the same PCI cannot be assigned more than once


- SM = 1: only **collision-free**

- SM = 2: **collision- and confusion free**  
(minimum requirement for proper PCI allocation)

- SM = 3, 4, etc. means an increased radius in which a PCI allocated may not be reused

- Higher SM → higher number of required PCIs

- Higher SM → “buffer” for the case that new adjacencies are formed later in the operational network (due to ANR discovery, additional cell deployment, etc.) → reduce required PCI reconfigurations



# Physical Cell ID (PCI) allocation


## Example algorithm: graph coloring

“How to assign a minimal number of colors to a graph in a way that no two neighboring nodes have the same color”




“How to assign a minimal number of PHY-CID in a cell cluster is a collision and confusion free way”

- Collision and confusion free → Construct the graph in such a way it includes the cell neighbors **and neighbors of neighbors**



# Multi-vendor PCI in HetNets: solution options




## Evaluation with planned HetNet scenarios


- base station type (either macro or pico) and position
- antenna azimuth, tilt, max. TX power parameters
- conducted a simulation based on path loss model and horizontal + vertical antenna characteristics to generate adjacency graph

Itf-N standards already support both options


A1



A2




A3




HetNet deployments 1 – 4 (no edges)


A4



A1




A2




HetNet deployments 1 – 4 (no edges)

A3



A4






# Number of required PCIs in different scenarios

## Continuous Allocation vs. Range Segmentation

**Safety Margin 2: collision- and confusion-free (minimum requirement for PCI allocation)**




**Range Segmentation:**  
some increase in required PCIs compared to Continuous Allocation, but not significant

# Number of required PCIs in different scenarios

## Continuous Allocation vs. Range Segmentation

Safety margin 5: collision- and confusion-free with extra safety “buffer” of 3



As the Safety Margin increases, Range Segmentation results in significantly lower number of required PCIs, in case there is a high number of inter-layer adjacencies (e.g., “A3” with 100 pico cells): these inter-layer adjacencies are a priori eliminated by Range Segmentation, but cause additional constraints for Continuous Allocation (pico cells connecting macro cells in the graph)

→ PCI range segmentation (combined with *different* per-domain PCI allocation algorithms) is viable in multi-vendor HetNets

# References

**S. Hämäläinen, H. Sanneck, C. Sartori (eds.)**

**LTE Self-Organizing Networks (SON) - Network Management Automation for Operational Efficiency, Wiley, ISBN 978-1-119-97067-5, December 2011. Chapter 4**

3GPP S5-091879 (n.d.) Nokia Siemens Networks, Starting Material for Automatic Radio Network Configuration Data Preparation, TSG-SA5 contribution.

[http://www.3gpp.org/ftp/tsg\\_sa/WG5\\_TM/TSGS5\\_64/Docs/S5-091879.zip](http://www.3gpp.org/ftp/tsg_sa/WG5_TM/TSGS5_64/Docs/S5-091879.zip) [accessed 20 March 2009].

3GPP TS36.331 (January 2010) Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol specification, 3rd Generation Partnership Project (3GPP).

3GPP TS23.401 (March 2010) General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access, 3rd Generation Partnership Project (3GPP).

3GPP TS32.501 (March 2010) Self-configuration of network elements; Concepts and Requirements, 3rd Generation Partnership Project (3GPP), (Release 9).

3GPP TR36.806 (March 2010) Relay architectures for E-UTRA (LTE-Advanced), 3rd Generation Partnership Project (3GPP).

3GPP TS32.502 (June 2010) Self-Configuration of Network Elements Integration Reference Point (IRP); Information Service (IS), 3rd Generation Partnership Project (3GPP), (Release 9).

3GPP TS32.532 (June 2010) Software Management Integration Reference Point (IRP); Information Service (IS), 3<sup>rd</sup> Generation Partnership Project (3GPP), (Release 9).

# References

3GPP TS33.310 (December 2010) Network Domain Security (NDS); Authentication Framework (AF), 3rd Generation Partnership Project (3GPP), (Release 10).

3GPP TS36.300 (March 2011) Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN), Overall Description, Stage 2, 3rd Generation Partnership Project (3GPP), (Release 10).

3GPP TS36.423 (March 2011) Evolved Universal Terrestrial Radio Access Network (E-UTRAN); X2 application protocol (X2AP), 3rd Generation Partnership Project (3GPP), (Release 10).

3GPP TS36.413 (March 2011) Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 Application Protocol (S1AP), 3rd Generation Partnership Project (3GPP), (Release 10).

3GPP TS25.484 (June 2011) Automatic Neighbour Relation (ANR) for UTRAN, Stage 2, 3rd Generation Partnership Project (3GPP), (Release 10).

3GPP TR32.511 (June 2011) Automatic Neighbour Relation (ANR) management; Concepts and requirements, 3<sup>rd</sup> Generation Partnership Project (3GPP), (Release 11).

3GPP TS36.211 (June 2011) Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Channels and Modulation, 3rd Generation Partnership Project (3GPP), (Release 10).

# References

- Ahmed, F., Tirkkonen, O., Peltomäki, M. et al. (2010) Distributed graph coloring for self-organization in LTE networks. Journal of Electrical and Computer Engineering, 2010.  
<http://www.hindawi.com/journals/jece/2010/402831/>[accessed 20 March 2010].
- Amirijoo, M., Frenger, P., Gunnarsson, F. et al. (2008) Neighbor cell relation list and physical cell identity self organization in LTE. IEEE International Conference on Communications Workshops, Beijing, China, 37–41.
- Bandh, T., Carle, G. and Sanneck, H. (2009) Graph coloring based physical-cell-ID assignment for LTE networks. 5<sup>th</sup> International Wireless Communications and Mobile Computing Conference, Leipzig, Germany, June.
- Bandh, T., Romeikat, R., Sanneck, H. et al. (2010) Optimized network configuration parameter assignment based on graph coloring. IEEE/IFIP Network Operations and Management Symposium, Osaka, Japan, April.
- Bandh, T. and Sanneck, H. (2011) Automatic Site Identification and Hardware-to-Site-Mapping for Base Station Self configuration, IEEE International Workshop on Self-Organizing Networks, Budapest, Hungary, May.
- Dahlen, A., Johansson, A., Gunnarsson, F. et al. (2011) Evaluations of LTE Automatic Neighbor Relations, IEEE International Workshop on Self-Organizing Networks, Budapest, Hungary, May.
- Eisenblätter, A., Türke, U., and Schmelz, C. (2011) Self-Configuration in LTE Radio Networks: Automatic generation of eNodeB parameters, IEEE International Workshop on Self-Organizing Networks, Budapest, Hungary, May.

# References

- Holma, H. and Toskala, A. (eds) (2010) LTE for UMTS: Evolution to LTE-Advanced, Revised Edition, Chapter on SON, John Wiley & Sons, Ltd, Chichester, UK.
- Horn, G., Forsberg, D., Moeller, W.D. and Niemi, V. (2010) Certificate Enrolment for Base Stations, Chapter 8.5, in LTE Security, John Wiley & Sons, Ltd, Chichester, UK.
- IETF RFC 2131, Droms, R. (1997) Dynamic Host Configuration Protocol, IETF, March.
- Lang, E., Redana, S. and Raaf, B. (2009) Business impact of relay deployment for coverage extension in 3GPP LTE advanced. IEEE International Conference on Communications, June.
- Lee, P., Jeong, J., Saxena, N. and Shin, J. (2009) Dynamic reservation scheme of physical cell identity for 3GPP LTE femtocell systems. Journal of Information Processing Systems, 5(4), S.207–S.219, [http://jips-k.org/dlibrary/JIPS\\_v05\\_no4\\_paper5.pdf](http://jips-k.org/dlibrary/JIPS_v05_no4_paper5.pdf).
- Sanneck, H., Bouwen, Y. and Troch, E. (2010a) Context based configuration management of Plug & Play LTE base stations. IEEE/IFIP Network Operations and Management Symposium, Osaka, Japan, April.
- Sanneck, H., Bouwen, Y. and Troch, E. (2010b) Dynamic radio configuration of self-organizing base stations. 7<sup>th</sup> International Symposium on Wireless Communication Systems, York, UK, September.
- Sanneck, H., Schmelz, C., Baumgarth, T. and Keutner, K. (2007) Network element autoconfiguration in a managed network. IFIP/IEEE Symposium on Integrated Management, Munich, Germany, May.
- Sanneck, H., Schmelz, C., Troch, E. and De Bie, L. (2009) Auto-connectivity and security setup for access network elements. IFIP/IEEE Symposium on Integrated Management, New York, NY, June.
- Szilagyi, P. and Sanneck, H. (2011) LTE relay self-configuration. IFIP/IEEE Symposium on Integrated Management, Dublin, Ireland, May.

# References

Szilágyi, P., Bandh, T., Sanneck, H. (2012), Physical Cell ID Allocation in Multi-layer, Multi-vendor LTE Networks, 4th International Conference on Mobile Networks and Management, September, Hamburg, Germany.

Szilágyi, P., Sanneck, H. (2013), Multi-vendor Auto-Connectivity in Heterogeneous Networks, IFIP/IEEE Symposium on Integrated Management, Ghent, Belgium, May.