

Reliable Operation of Heterogeneous Wireless Networks with SON (Self-Organizing Networks) - Self-Healing

Henning Sanneck, Szabolcs Nováczki

Nokia Siemens Networks
- Research

Tutorial DRCN 9th International Conference on
Design of Reliable Communication Networks



Self-healing: background

- NGMN use case doc emphasizes „sleeping cell“ detection / recovery
- TMO/VDF „NGMN operations requirements“ doc 12/09:
„quality and quantity of alarms“
among Top 10 requirements
- Pain point (cf. Questionnaire on troubleshooting):
missing detection & diagnosis functionality



NGMN Operations Requirements

Top ten network operations requirements for multi-vendor, multi-technology environment

Vodafone / T-Mobile

Release 1.0


OPREQ-2009-01

6. What are your most important pain points during your work?

- Problems that cannot be directly solved through alarms (HW or SW failure?)
- Problems that cannot be seen from the alarms

Human operator work effort distribution: example

Self-healing



Cell Anomaly Detection:

- profiles a cell
- monitors cell “health”
- triggers diagnosis in case of detection

Degradation Diagnosis: identify root cause based on embedded operational knowledge and training (technologies: data mining, machine learning)

Recovery: choose action (e.g., cell reset, compensation) with best utility

Self-healing: key requirements

Realistic prerequisites


Take into account the information that is available from operators.

Seamless integration


Integrate into the operator's current troubleshooting process.

Adaptation


Adaptation to the operator's network (no universal expert knowledge).



Feasibility



Acceptance




Flexibility

Self-healing: basics

Operational status




actions



→ Requirement to determine the operational status (**detection** by analysis of (combinations of) KPIs & alarms), establish the cause (**diagnosis**) and decide / execute actions (**recovery**)

Self-healing: basics




Technologies	Time-series analysis / modelling → profiling - prediction-based - window-based (similarity measure)	Alarm correlation Probabilistic Graph Models (Bayesian Networks) Case Based Reasoning, Self-Organizing Maps Neural Networks	Decision Theory Policies
--------------	--	---	-----------------------------

Goals of **automatic** cell anomaly detection and diagnosis → OPEX saving

- Reduction of workload for human troubleshooting experts
→ free time for the really crucial problems
- Reduce time until a degradation / outage is detected and diagnosed
→ early trigger of actions


Self-healing: basics

Example: sleeping cell diagnosis and recovery




Research work: not technology research, but adaptation of technology to use case / domain

Self-healing: cell anomaly detection



Degraded cell: examples

- SW problem (version change) → sleeping cell
- HW problem (power degradation) w/o alarm → coverage hole
- Mis-configuration → interference
- Environmental change → shadowing



- Reliable detection (localization) of incidents which would otherwise be detected too late or missed entirely
- Reduced human work effort

Self-healing: cell anomaly detection

Problems with state-of-the-art

Using thresholds and binary alarms

- to the operator, a KPI looks either 100% good (no alarm) or 100% bad (alarm); however, the state of the network is not black and white
- a small change in the state of the system results in a big step in detection (i.e., sending an alarm)

Human operator is involved at an early stage

- has to calibrate thresholds separately for each KPI
- has to manually infer (i.e., diagnose) what is the problem based on the alarms

Self-healing: cell anomaly detection


KPI-level concept

Detection is based on profiles

Detection should notice if the behavior of a KPI corresponds to or differs from its usual behavior, that is, the profiled value. However, there is no strict threshold and no alarm is sent.

Unified KPI level concept

The level of each KPI is between 0 and 1, indicating the significance of deviation from the usual behavior. All KPIs can be leveled by the same concept, regardless of the specific type and semantics of the KPI.



KPI level as function of deviation



level \rightarrow 0

behaves according to profile





level \rightarrow 1


significant deviation from profile

Nokia Siemens Networks

Self-healing: profiling for cell anomaly detection



Cell Anomaly Detection: performance metrics



- Detection **accuracy**: (→ reduce human workload)
 - False negatives, true positives: (un-)detected anomalies (for performance evaluation 100% knowledge of cases (symptom) required) → difficult to acquire data → simulation)
 - False positives (can be evaluated with available data known to be fault free)
- Detection **speed**: (→ reduce time until detection)

Cell Degradation Diagnosis


Challenge in linking symptoms to problem causes

- Problems can start in any part of the network; hardware, software, attached systems, or applications
- There is not always a direct indication (alarm, trap) of a problem (→ detection)
- A single problem often causes many symptoms in many related (or even not closely related) elements
- Different problems can cause overlapping symptoms
- Problems can escalate, symptoms can trigger further symptoms in related objects, making necessary to examine all symptoms across related elements to identify the root cause
- Network elements or software from different vendors have different bugs
- Even different software versions from the same vendor have different bugs
- Usually there is **no knowledge database (relating symptoms to problems)**, which makes automation difficult


Problems with the state-of-the-art:

- Manual diagnosis, based on alarms
- Too many and too low level events/alarms
- Deduplication, filtering: no built-in intelligence, does not offer any root cause analysis

Self-healing: Integrated Detection / Diagnosis Framework



→ DRCN paper: Szabolcs Nováczki „An Improved Anomaly Detection and Diagnosis Framework for Mobile Network Operators”, session “Reliability of Wireless Access”, Wednesday, 6.3., 15.20-16.40



Cell Anomaly Detection and Degradation Diagnosis Demo


An example application showcase:

- 70 3G cells of a live network**
- 12 KPIs/cell**
- 188 days data with hourly granularity**

**for a
world
in motion™**



Learning Mode




Learning Mode

Anomaly Detection Module learns the normal (i.e., no fault, no symptom) operation states – semi-supervised learning or manual

Diagnosis Module learns the patterns of known faults - manual

Symptom patterns


- Symptom pattern – which KPIs are normal and which are abnormal
- Different faults have different fault patterns



- Multiple profiles for each KPI
- Only normal samples are used to create the profiles


Learning Mode

- KPIs are calculated at certain granularity.
- Manual troubleshooting process is triggered by an alarm.
- The operator analyzes KPIs (monitoring tools) and identifies the root cause of the fault.
- The identified faults are stored in the fault pattern database
 - Each record tells whether a KPI was affected by the associated fault or not.
- In normal operation periods the profiles of the KPIs are learned



- Multiple profiles for each KPI
- Only normal samples are used to create the profiles

Anomaly Detection



Monitoring Mode

- The anomaly detection analyzes each KPI; comparing them to the associated profiles.
- The detection result is a KPI-level assigned to each KPI
 - The KPI-level is a normalized $[0,1]$ measure of the distance of the actual KPI value from the profiles.
- KPI-level vector (level value of each KPI) is passed to the diagnosis module
- Read attached paper for more details:




Monitoring Mode

Anomaly Detection Module

- identifies worst performing cells
- identifies worst performing KPIs – actual KPI pattern

Diagnosis Module


- finds most plausible explanation of the actual KPI pattern



The FEEDBACK of the operator helps to improve anomaly detection and diagnosis performance by converging results to operator expectations

Monitoring Mode

- The anomaly detection analyzes each KPI; comparing them to the associated profiles.
- The detection result is a KPI-level assigned to each KPI.
 - The KPI-level is a normalized $[0,1]$ measure of distance of the actual KPI value from the profiles.
- KPI-level vector (level values of each KPI) is passed to the diagnosis module
- Read attached paper for more details:



- The KPI-level vector is the actual symptom pattern of the network element
 - Shows which KPIs are close to the profile and which are far
 - During normal operation all KPI-level is close to zero
- The actual symptom pattern is compared to the known patterns
 - The most similar pattern is the most plausible explanation of the detected anomaly
- Read attached paper for more details:



Diagnosis

The FEEDBACK of the operator helps to improve anomaly detection and diagnosis performance by converging results to operator expectations

References

S. Hämäläinen, H. Sanneck, C. Sartori (eds.)

LTE Self-Organizing Networks (SON) - Network Management Automation for Operational Efficiency, Wiley, ISBN 978-1-119-97067-5, December 2011. Chapter 6

3GPP TS32.541 (September 2010) Telecommunication Management; Self-Organizing Networks (SON); Self-Healing Concepts and Requirements, 3rd Generation Partnership Project (3GPP), (Release 10).

3GPP TS32.762 (December 2010) Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS), (Release 10).

3GPP TS32.766 (December 2010) Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions, (Release 10).

3GPP TS32.522 (January 2011) Self-Organizing Networks (SON) Policy Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS), 3rd Generation Partnership Project (3GPP), (Release 10).

3GPP TS32.526 (January 2011) Self-Organizing Networks (SON); Policy Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions, (Release 10).

3GPP TS32.410 (April 2011) Telecommunication management; Key Performance Indicators (KPI) for UMTS and GSM, 3rd Generation Partnership Project (3GPP), (Release 10).

References

- Amirijoo, M., Jorguseski, L., Litjens, T. and Schmelz, C. (2011) Cell outage compensation in LTE networks; Algorithms and performance assessment. IEEE International Workshop on Self-Organizing Networks, May, Budapest.
- Barco, R., Diez, L., Wille, V. and Lazaro, P. (2007) Automatic Diagnosis of Mobile Communication Networks under Imprecise Parameters, Series on Expert Systems with Application, Elsevier: Amsterdam.
- Barco, R., Lazaro, P., Diez, L. and Wille, V. (2008) Continuous versus Discrete Model in Autodiagnosis Systems for Wireless Networks. IEEE Transactions on Mobile Computing, 7(6), 673–681. doi: 10.1109/TMC.2008.23.
- Barco, R., Wille, V. and Diez, L. (2005) System for automated diagnosis in cellular networks based on performance indicators. European Transactions on Telecommunications, 16(5), 399–409.
- Barreto, G.A., Mota, J.C.M., Souza, L.G.M. et al. (2004) A new approach to fault detection and diagnosis in cellular systems using competitive learning. Proceedings of the VII Brazilian Symposium on Neural Networks (SBRN'04).
- Bod'ik, P., Friedman, G., Biewald, L. et al. (2005) Combining visualization and statistical analysis to improve operator confidence and efficiency for failure detection and localization. IEEE Proceedings of International Conference on Autonomic Computing (ICAC 05), pp. 89–100.
- Chandola, V., Banerjee, A. and Kumar, V. (2009) Anomaly detection: A survey. ACM Computer Survey, 41(3), Article 15 (July 2009) 58. doi: 10.1145/1541880.1541882, <http://doi.acm.org/10.1145/1541880.1541882>.

References

- Cheung, B., Kumar, G. and Rao, S. (2005) Statistical algorithms in fault detection and prediction: Toward a healthier network. *Bell Labs Technical Journal*, 9(4), 1538–7305.
- Khanafer, R.M., Solana, B., Triola, J. et al. (2008) Automated diagnosis for UMTS networks using bayesian network approach. *IEEE Transactions on Vehicular Technology*, 57(4), 2451–2461. doi: 10.1109/TVT.2007.912610.
- Laiho, J., Raivio, K., Lehtimäki, P. et al. (2005) Advanced analysis methods for 3G cellular networks. *IEEE Transactions on Wireless Communications*, 4(3), 930–942.
- Laiho, J., Wacker, A. and Novasad, T. (2006) *Radio Network Planning and Optimization for UMTS*, 2nd edn, John Wiley & Sons, Inc., New York.
- Mueller, C., Kaschub, M., Blankenhorn, C. and Wanke, S. (2008) A cell outage detection algorithm using neighbor cell list reports. In K.A. Hummel and J.P.G. Sterbenz (eds.), *IWSOS 2008, LNCS5343*, 218–229.
- Novaczki, S. and Szilagyi, P. (2011) Radio Channel Degradation Detection and Diagnosis Based on Statistical Analysis. 1st IEEE International Workshop on Self-Organizing Networks, May, Budapest.
- Szilagyi, P.; Novaczki, S. (2012) An Automatic Detection and Diagnosis Framework for Mobile Communication Systems, Network and Service Management, *IEEE Transactions on*, vol.9, no.2, pp.184-197, June.
- Novaczki, S.; Szilagyi, P. (2012) An Intelligent Anomaly Detection and Diagnosis Assistant for Mobile Network Operators, 2nd IEEE International Workshop on Self-Organizing Networks, August, Paris.

References

- Nováczki, S. (2013), “An Improved Anomaly Detection and Diagnosis Framework for Mobile Network Operators”, 9th International Conference on Design of Reliable Communication Networks (DRCN 2013), Budapest, March.
- Rao, S. (2006) Operational Fault Detection in cellular wireless base-stations. IEEE Transactions on Network and Service Management, 3(2), 1–11.
- Salfner, F., Lenk, M. and Malek, M. (2010) A survey of online failure prediction methods. ACM Computer Survey, 42(3), 42. doi: 10.1145/1670679.1670680, <http://doi.acm.org/10.1145/1670679.1670680>.
- Van den Berg, J.L., Litjens, R., Eisenblatter, A. et al. (2008) SOCRATES: Self-Optimisation and self-ConfigurATion in wirelESs networks, COST 2100 4th MCM, February 6–8 2008, Wroclaw.
- Wietgreffe, H., Tuchs, K.D., Jobmann, K. et al. (1997) Using neural networks for alarm correlation in cellular phone networks. International Workshop on Applications of Neural Networks to Telecommunications (IWANNT), pp. 248–255.
- Zanier, P., Guerzoni, R. and Soldani, D. (2006) Detection of Interference, Dominance and Coverage Problems in WCDMA Networks. IEEE 17th International Symposium on Personal, Indoor and Mobile Radio Communications, 11–14 September 2006, pp. 1–5.
- Frenzel, C., Sanneck, H., Bauer, B. (2012), Automated Rational Recovery Selection for Self-Healing in Mobile Networks, 2nd IEEE International Workshop on Self-Organizing Networks, August, Paris.
- Frenzel, C., Sanneck, H., Bauer, B. (2013), Rational Policy System for Network Management, IFIP/IEEE Symposium on Integrated Management, Ghent, Belgium, May.